

|                                 |  |            |
|---------------------------------|--|------------|
| <b>1. Product- And Company</b>  | <b>Issue Date</b>  | 16.09.2009 |
| <b>1.1 Trade Name</b>           | <b>FS-1028 MFP</b>   |            |
| <b>1.2 Company</b>              | <i>Kyoceramita Europe B.V., Otto-Hahn Strasse 12, D-40670 Meerbusch</i>  |            |
| <b>1.3 Phone</b>                | <b>+49-(0)2159-928-421</b>   |            |
| <b>2. Safety Approvals</b>      | <b>Safety 73/23/EEC<br/>EMC 89/336/EEC</b>   |            |
| <b>3. Environment Approvals</b> |  |            |
| <b>4. Power Consumption</b>     | <b>Printing: 494 W<br/>Stand By: 88 W<br/>Sleep Mode: 9.3 W</b>  |            |
| <b>5. Installation Notes</b>    | <i>The machine should be placed more than 35cm from the wall with a minimum of left 50cm / right 50cm space for operation and maintenance. Sufficient ventilation should be provided. The machine should not be placed in a dusty room or where ammonia gas is in use.</i> |            |
| <b>6. Room Humidity</b>         | <b>20 % – 80 %</b>   |            |
| <b>7. Room Temperature</b>      | <b>10 °C – 32.5 °C</b>   |            |
| <b>8. Noise Level</b>           | <b>Printing: 64.7 dB (A) L<sub>WA</sub>d [RAL UZ 122]<br/>Stand By: 42.1 dB (A) L<sub>WA</sub> [RAL UZ 122]<br/>Sleep Mode: N.A.</b>   |            |
| <b>9. Light Source</b>          | <b>Exposure Original: N.A.<br/>Exposure Drum: Semiconductor Laser</b>  |            |
| <b>10. Emissions</b>            | <b>Ozone: 0.690 mg/h [RAL UZ 122]<br/>Fine Dust: 1.5 mg/h [RAL UZ 122]<br/>Styrene: 0.15 mg/h [RAL UZ 122]<br/>Benzene: 0.032 mg/h [RAL UZ 122]<br/>TVOC: 8 mg/h [RAL UZ 122]</b>  |            |
| <b>11. Others</b>               |  |            |