

1. Product- And Company	Issue Date	18.01.2009		
1.1 Trade Name	FS-C5100DN / FS-C5200DN / FS-C5300DN			
1.2 Company	<i>Kyoceramita Europe B.V., Otto-Hahn Strasse 12, D-40670 Meerbusch</i>			
1.3 Phone	+49-(0)2159-928-421			
2. Safety Approvals	Safety 73/23/EEC EMC 89/336/EEC			
3. Environment Approvals	Meet criteria of RAL UZ-122			
4. Power Consumption	Print Mode: 420 / 420 / 477 W Stand By Mode: 70 / 70 / 79 W Sleep Mode: 7 / 7 / 7 W			
5. Installation Notes	<i>The machine should be placed more than 40 cm from the wall with a minimum of left 30 cm/right 30 cm/front 100cm space for operation and maintenance. Sufficient ventilation should be provided. The machine should not be placed in a dusty room or where ammonia gas is in use.</i>			
6. Room Humidity	20 % – 80 %			
7. Room Temperature	10.0 °C – 32.5 °C			
8. Noise Level	Printing: 66.0 / 66.0 / 66.0 dB(A) Lwad RAL UZ 122 Stand-by: 46.8 / 46.8 / 46.8 dB(A) Lwa RAL UZ 122 Sleep modus: not measurable			
9. Light Source	Exposure Drum: Semiconductor Laser			
10. Emissions	Ozone:	B/W:	Colour:	RAL UZ 122
	Styrene:	1.0/1.0/0.8 mg/h	1.1/1.1/1.2 mg/h	
	Benzene:	0.007/0.007/0.06 mg/h	0.009/0.009/0.09 mg/h	
	TVOC:	0.01/0.01/0.012 mg/h	0.002/0.002/0.012 mg/h	
	Dust:	1.2/1.2/2.5 mg/h	1.08/1.08/3.18 mg/h	
11. Others		0.77/0.77/>0.018 mg/h	<0.018/<0.018/0.73 mg/h	